

3M Construction & Home Improvement Markets

Product Information Sheet

Issue : April 2019

Replace : January 2019

Scotch Extremium Ultra tape

Description



Scotch Extremium Ultra duct tape is a super thick tape for super tough jobs. It is ultra thick with a water resistant backing. It can be used for: repairing, holding, sealing and protecting metal parts and surfaces. Its aggressive, natural rubber adhesive grips instantly to a variety of surfaces including metal, glass, plastic and sealed concrete.

Product Characteristics	
Backing	Polyethylene film over cloth scrim
Adhesive	Natural Rubber-based adhesive
Standard Roll length	48mm x 25m and 24mm x 10m
Color	Black

Typical Physical Properties	value	Method
Total thickness	430 μ m	ASTM D-3652
Adhesion to stainless steel	9.3 N/cm	ASTM-D3330
Tensile strength	67 N/cm	ASTM-D3759
Elongation at break	18 %	ASTM-D3759

The values displayed are the result of illustrative lab test measures made according to the indicated external norm and shall not be considered as a commitment from 3M

Storage

To obtain best performances, store this product under normal condition of 21°C and 50% relative humidity in the original packaging and use it within one year from date of purchase.

Warning

Apply above 10°C and up to 70°C-

Do not use on wallpaper or other delicate surfaces, Do not use on poorly bonded surfaces

3M Construction & Home Improvement Markets Product Information Sheet

In case of doubt, test before use

2/2

Features/advantages/Benefits

Features	Advantages	Benefits
Rubber adhesive	Instant adhesion	Stick easily to the surface
	Very Good holding power Long lasting	Helps resist lifting or curling, Holds in many applications with strength constraints
PE over cloth scrim	Hand tearable in both side	Easy handling
	Very narrow scrim	Very High resistance
	2 times thicker than other 3M duct tapes	Strong holding power and high resistance
	High tensile strength for demanding application	



Important notice :

The use of the 3M product described within this document assumes that the user has read and understood the user notice. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected purpose.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the 3M product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M group (which cannot verify or control those elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for 3M products are determined with the sales contract documents and with the mandatory and applicable clause, excluding any other warranty or compensation